

Briggs & Stratton Gasoline Engines

Basic Models	Dates of Manufacture (month-year)	HP	RPM	Torque (lb/ft)	BMEP	Bore	Stroke	CID	Piston Speed (ft/min)
A	2-33 to 8-48	1-3/4	3,200	2.87	48.6	2-1/4	2-1/4	8.9	1,200
B	9-34 to 11-47	2-3/4	3,200	4.51	47.9	2-5/8	2-5/8	14.2	1,400
F	7-21 to 4-23	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
FB	6-23 to 11-24	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
FC	1-24 to 6-25	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
FE	1-25 to 11-25	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
FG	1-27 to 10-27	3/4	1,900	2.07	35.1	2-1/4	2-1/4	8.9	712.5
FH	11-25 to 10-33	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
FI	12-27 to 1-33	3/4	1,900	2.07	35.1	2-1/4	2-1/4	8.9	712.5
H	7-32 to 11-40	1/2	1,950	1.34	22.7	2-1/4	2-1/4	8.9	731
I	1-40 to 6-49	3/4	3,200	1.23	39.5	2	1-1/2	4.7	800
K	2-33 to 12-40	3	2,700	5.83	45.5	2-3/4	3-1/4	19.3	1,462.5
L	1-30 to 12-32	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
M	5-30 to 3-34	1	2,400	2.19	39.1	2-1/4	2-1/4	8.9	900
N	11-40 to 5-55	2	3,600	2.92	69.9	2	2	6.3	1,200
NS	11-40 to 5-55	1	3,200	1.64	39.3	2	2	6.3	1,066.6
PB	12-23 to 2-35	1	2,400	2.19	26.8	2-1/2	2-1/2	12.3	900
Q	11-25 to 11-33	1-1/2	2,400	3.28	25.6	2-3/4	3-1/4	19.3	1,300
R	4-29 to 10-33	3	2,400	6.56	51.2	2-3/4	3-1/4	19.3	1,300
S	6-30 to 11-33	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
T	8-30 to 5-31	1/2	1,800	1.46	24.7	2-1/4	2-1/4	8.9	675
U	9-40 to 9-45	1	3,200	1.64	39.3	2	2	6.3	1,066.6
W	6-31 to 5-32	1-1/2	2,400	3.28	25.6	2-3/4	3-1/4	19.3	1,300
WI	10-38 to 5-50	1/2	3,000	.875	28.1	2	1-1/2	4.7	750
WM	8-36 to 12-40	1/2	3,000	.875	28.1	2	1-1/2	4.7	750
WMB	10-38 to 6-57	2/3	2,250	1.54	49.4	2	1-1/2	4.7	562.5
WMI	8-36 to 12-40	1/2	3,000	.875	28.1	2	1-1/2	4.7	750
Y	8-31 to 9-39	1/2	1,900	1.38	23.4	2-1/4	2-1/4	8.9	712.5
Z	8-31 to 12-48	5	3,200	8.21	53.8	3	3-1/4	23.0	1,733.3
ZZ	8-31 to 12-48	6	3,200	9.85	64.6	3	3-1/4	23.0	1,733.3
SS	3-49 to 1-57	1-1/10	3,200	1.80	57.7	2	1-1/2	4.7	800
6	6-49 to 7-58	2	3,600	2.92	69.9	2	2	6.3	1,200
8	8-49 to 7-58	2-1/2	3,200	4.10	78.3	2-1/4	2	7.9	1,066.6
9	8-48 to 12-62	3-1/10	3,200	5.09	86.2	2-1/4	2-1/4	8.9	1,200
14	3-48 to 9-63	5-1/10	3,200	8.37	88.9	2-5/8	2-5/8	14.2	1,400
19	1-57 to 8-65	7-1/5	3,200	11.8	96.2	3	2-5/8	18.5	1,400
23	1-48 to 8-65	8-1/4	3,200	13.5	88.5	3	3-1/4	23.0	1,733.3
61100		2	3,600	2.92	66.2	2-3/4	1-1/2	6.65	900
61100		1.79	3,000	3.14	71.2	2-3/8	1-1/2	6.65	750